

AP 5.4 TABLETOP LABEL PRINTER

Industrial label printer for medium label volume applications.
Guarantee for perfect printed text, barcodes and logos for any industry.

FLEXIBLE DISTRIBUTION CENTER PRINTING

The AP 5.4 Printer combines high throughput with high quality print results, increasing efficiency for compliance labeling applications for distribution centres, including:

- Box labeling
- Shipping labeling
- Compliance labeling
- Product identification

IMPROVE TRACEABILITY

The AP 5.4 enables you to print bar codes, serial numbers, images and text on a wide variety of materials, from paper to plastic improving label traceability. The AP 5.4 is a flexible printer as it can use multiple media types from 15 mm up to 120 mm in size in either dispensed or batch modes while maintaining high print quality at all times.

INCREASE PRODUCTIVITY

This extremely versatile generation of printers can increase productivity by up to 30%, which is achieved by enhanced processing power and best-in-class first-label-out-time. These benefits are noted across both distributed and batch printing applications.

ENSURE COMPLIANCE

- Smaller font options enable you to add more information to your labels, ensuring compliance and consistency across the global supply chain.
- Adding GS1 GDSN 2 standard bar codes and multi-lingual label information becomes straightforward and cost-effective with this multipurpose printer.

MORE INFORMATION

To learn more about our AP 5.4 Tabletop Bar Code Printer or to receive complete warranty information as well as other terms and conditions, please contact your NOVEXX Solutions representative, e-mail to printers@novexx.com or visit our website at www.novexx.com.



AP 5.4 TABLETOP LABEL PRINTER

STANDARD FEATURES

DIMENSIONS

Height: 272 mm (10.70")
Width: 260 mm (10.23")
Depth: 462 mm (18.18")

WEIGHT

14kg

PRINTING METHOD

Thermal direct/transfer

PRINTHEAD

203 or 300 dpi

MEMORY

ROM: 4 MB Flash
RAM: 64 MB SDRAM

BAR CODES

EAN 8, EAN 13 with add-on 2 and 5; UPC-A, UPC-E; Code 39; Code 39 extended; Code 39 Ratio 3:1; Code 39 Ratio 2,5:1; ITF, Codabar; Code 128 A, B, C; Code 128 UPS; Code 128 Pharmacy; Code 2/5 Matrix; Code 2/5 Interleaved; Code 2/5 5; Code 2/5 Interleaved Ratio 1:3; Code 2/5 Matrix Ratio 1:2,5; Code 2/5 Matrix Ratio 1:3; MSI; EAN 128; Postcode (Guide and Identity Code); All bar codes scalable in 16 widths and height; 2-dimensional Data Matrix Code; Maxi Code; PDF 417; Codablock F; Code 49; QR Matrix Code; GS1 Databar; EAN/UCC composite symbology

STANDARD FONTS

17 fonts including OCR-A and OCR-B; three scalable fonts, TrueType® fonts (also unencoded) supported. All font types can be stored on an SD card.

FONT MAGNIFICATION

Rotation by 0°, 90°, 180° and 270°. Up to factor 8 scaling in X/Y direction.

KEYPAD/DISPLAY

Illuminated LCD graphics display with two lines of 16 characters.

CONSUMABLES

Only NOVEXX Solutions supplies are recommended.

LABEL SIZES

Width: 15mm to 120mm (0.59" to 4.72")

LABEL ROLL SIZE

OD: up to 210mm (up to 8.26") Core
Diameter: 38mm, 76mm, 102mm
(1.50", 3" 4")

MIN/MAX MATERIAL THICKNESS

Self-adhesive labels: 60-160 gsm
(0.13lbs - 0.35lbs)
Cardboard labels: max 240 gsm (0.53 lbs)

RIBBON LENGTH

Up to 500m (1640.19')

RIBBON WIDTH

25mm to 110mm (0.98" to 4.33")

ENVIRONMENTAL RANGES

OPERATING TEMPERATURE

5° to 40°C (41° to 104°F)

HUMIDITY/OPERATING AND STORAGE

5% to 90% non-condensing.

ELECTROSTATIC DISCHARGE AND AIR QUALITY

Some problems with electronic equipment may occur in environments prone to static discharge or extreme dust conditions. NOVEXX Solutions suggests that you take precautions to minimize these problems.

PERFORMANCE

POWER SOURCE

100 - 240 V (AC); Mains frequency
60/50 Hz

PRINT SPEED

50-200 mm/s for 203 dpi
50-150 mm/s for 300 dpi

COMMUNICATIONS

STANDARD COMMUNICATION PORTS

10/100 Base-T Ethernet
2 x USB
RS232 Serial

OPTIONS

- Cutter
- Internal rewinder
- External rewinder
- Dispenser light barrier
- Keyboard
- SD card

In our ongoing effort to deliver the best technology, specifications are subject to change without notice.

Novexx Solutions GmbH DEUTSCHLAND

Ohmstrasse 3
D-85386 Eching
Tel. +49 (0)8165 925 299
info.deutschland@novexx.com

Novexx Solutions S.A.S. FRANCE

Tel. +33 (0)825 82 61 52
info.france@novexx.com

Novexx Solutions B.V. NEDERLAND

Tel. +31 (0)302 63 22 33
info.nederland@novexx.com

Novexx Solutions B.V. BELGIE

Tel. +32 (0)2 377 8002
info.belgie@novexx.com

Novexx Etiketleme Sistemleri Tic. A.Ş. TÜRKIYE

Tel. +90 216 564 81 81
info.turkiye@novexx.com

Novexx Solutions GmbH ITALIA

Tel. +39 0331 1855511
info.italia@novexx.com

Novexx Solutions GmbH FILIAL SVERIGE

Tel. +46 (0)31 68 30 40
info.sverige@novexx.com

manroland India Pvt. Ltd. INDIA

Tel. +91 (11) 47002900
info.india@novexx.com

Novexx Solutions USA

Tel. +1 610 4730751
info.usa@novexx.com

Novexx Solutions ASIA

Tel. +86 (021) 2215 7665
info.asia@novexx.com

Novexx Solutions GmbH POLSKA

Tel. +48 (0)605957108
info.polska@novexx.com

The information contained herein is believed to be reliable but NOVEXX Solutions makes no representations concerning the accuracy or correctness of the data. The information, like any other should be confirmed independently for the particular end user conditions to ensure the proposed labeling meets the relevant requirements and regulations. NOVEXX Solutions shall have no liability whatsoever, regardless of any legal theory, arising out of your use or reliance on the information contained herein and in no event shall NOVEXX Solutions be held liable for consequential, indirect or incidental damages. NOVEXX Solutions liability is limited to the replacement value of defective product. Products, information and specifications are subject to change without notice.

© 2015 Novexx Solutions GmbH, All Rights Reserved. Third party trademarks and/or trade names may be used herein are the property of their respective owner(s).